AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT			1. CONTRACT ID K	CODE F	AGE OF	PAGES
2. AMENDMENT/MODIFICATION NO. P00007	B. EFFECTIVE DATE JULY 07, 2003	4. REQUISITION/PUR		5. PROJECT N	NO. (If applic	able)
6. ISSUED BY CODE		7. ADMINISTERED BY	((If other than Iter	n 6) CODE		
DEFENSE ENERGY SUPPORT CENTER 8725 JOHN J. KINGMAN RD., SUITE 4950 FORT BELVOIR, VA 22060-6222 BUYER/SYMBOL - GLORIA J. EDMONDS PHONE: (703) 767-9519 FAX (703) 767-8						
8. NAME AND ADDRESS OF CONTRACTOR (No.		d ZIP Code)	9A. AMEND	MENT OF SOLI		0.
				SPU000-02-R-0	JU37-UUU1	
			X 9B. DATED	(SEE ITEM 11)		
				MARCH 2	7, 2003	
			10A. MODIF	ICATION OF C	ONTRACT/O	RDER NO.
			10B. DATE) (SEE ITEM 13	,	- AAARA
	FACILITY CODE	A)	2110		
	ONLY APPLIES TO			7		
The above numbered solicitation is amended as set				is extended,		extended.
Offer must acknowledge receipt of this amendment prior	to the hour and date specified	in the solicitation or as a	mended, by one of th	ne following meth	ods:	
(a) By completing Items 8 and 15, and returning submitted; or (c) By separate letter or telegram which incl RECEIVED AT THE PLACE DESIGNATED FOR THE RECEIV virtue of this amendment you desire to change an offer all the solicitation and this amendment, and is received prior 12. Accounting and Appropriation Data (If require	udes a reference to the solicit PT OF OFFERS PRIOR TO THE eady submitted, such change to the opening hour and date	HOUR AND DATE SPEC may be made by telegra	mbers. FAILURE OF '	YOUR ACKNOWL N REJECTION OF	EDGMENT TO YOUR OFFER	BE . If by
N/A						
	PLIES ONLY TO MO					
IT MODIFIES T (X) A. THIS CHANGE ORDER IS ISSUED PURSUANT TO 10A.	HE CONTRACT/ORD : (Specify authority) THE CHA				ORDER NO. I	N ITEM
B. THE ABOVE NUMBERED CONTRACT/ORDER IS appropriation date, etc). SET FORTH IN ITEM 14,				s in paying office,		
C. THIS SUPPLEMENTAL AGREEMENT IS ENTERED	INTO PURSUANT TO AUTHO	DRITY OF:				
D. OTHER (Specify type of modification and authority	yl					
E. IMPORTANT: Contractor is not,	is required to sign this docu			the issuing office		
14. DESCRIPTION OF AMENDMENT/MODIFICATION	ON (Organized by UCF see	ction headings, includ	ling solicitation/con	tract subject m	atter where	feasible.)
\$	SEE ATTACHED					
Except as provided herein, all terms and condition force and effect.	s of the document referen	ced in Item 9A or 10	A, as heretofore ch	nanged, remains	unchanged	and in full
15A. NAME AND TITLE OF SIGNER (Type or print)	16A. NAME AND T	ITLE OF CONTRAC	TING OFFICER	(Type or prin	nt)
		DAVID W. P	ETERSON			
15B. CONTRACTOR/OFFEROR	15C. DATE SIGNED	16B. UNITED STAT	ES OF AMERICA		16C. DATE	SIGNED
(Signature of person authorized to sign)	-	(Signa	ture of Contracting O	fficer)		

- A. ACKNOWLEDGEMENT OF AMENDMENTS: ALL OFFERORS MUST ACKNOWLEDGE RECEIPT AND ACCEPTANCE OF ALL AMENDMENTS TO THE SOLICITATION. YOU MAY DO THIS BY SIGNING (BLOCK 15A, B AND C OF STANDARD FORM 30) AND RETURNING THE AMENDMENT OR BY WRITTEN ACKNOWLEDGEMENT OF RECEIPT AND ACCEPTANCE AS PART OF THE PROPOSAL SUBMISSION PACKAGE. PLEASE BE CERTAIN TO IDENTIFY ANY EXCEPTIONS TO THE SOLICITATION'S TERMS AND CONDITIONS.
- B. ADD THE FOLLOWING CLAUSE IS HEREBY ADDED TO THE SOLICITATION AND REPLACES CLAUSE C16.27 DATED (APR 2001). THIS CLAUS APPLIES TO BIODIESEL REQUIREMENTS ONLY.

C16.27 FUEL, BIODIESEL (B20) (DESC JUN 2003)

Offered product shall conform to the following requirements that define a fuel suitable for use in automotive diesel engines.

- (a) **PRODUCT COMPOSITIONAL REQUIREMENTS.** Product shall consist of a blend of 20 percent (plus or minus one percent) virgin vegetable oil blendstock conforming to the requirements of ASTM D 6751 and 80 percent minimum low sulfur diesel fuel oil conforming to ASTM D 975, grade low sulfur number 1-D or grade low sulfur number 2-D.
- (b) **PRODUCT PERFORMANCE REQUIREMENTS.** The finished biodiesel blend shall conform to the following requirements:

TEST	<u>METHOD</u>	<u>VALUE</u>
1. Appearance	ASTM D 4176, Procedure 1	Clear & Bright
2. Acid Number, mg KOH/g	ASTM D 664	0.2 max.
3. Density at 15°C, kg/L	ASTM D 4052 ASTM D 1298	0.86 - 0.90
4. Viscosity, mm/S at 40°C	ASTM D 445	1.3 - 4.1
5. Flashpoint, ^o C	ASTM D 93	Apr - Sep: 52 min. Oct - Mar: 38 min.
6. Cloud point, ^o C	ASTM D 2500	see (c) below
OR Cold Filter Plugging Point, ^o C	ASTM D 6371	see (c) below
7. Sulfur Content, mass %	ASTM D 2622	0.05 max.
8. Distillation Temperature, ^o C 90% evaporated	ASTM D 86	338 max.
9. Carbon Residue on 10% bottoms, mass %	ASTM D 524	0.35 max.
10. Cetane Number	ASTM D 613	40 min.
11. Ash Content, mass%	ASTM D 482	0.01 max.

12. Water and Sediment, volume%

ASTM D 2709

0.05 max.

13. Copper Corrosion, 3 hours @ 50°C

ASTM D 130

No. 3 max.

- (c) **PRODUCT LOW TEMPERATURE PERFORMANCE.** The lower temperature performance of the B20 shall be defined by one of the following two properties: Cloud Point or Cold Filter Plugging Point (CFPP). Unless a more restrictive cloud point limit is specified in the contract schedule, the cloud point tested in accordance with ASTM D 2500 shall be equal to or lower than the tenth percentile minimum ambient temperature in the geographical area and seasonal timeframe in which the B20 is to be used, as specified in Appendix X4 of ASTM D 975. Unless a more restrictive CFPP limit is specified in the contract schedule, the maximum CFPP of the B20 shall be a minimum of 10 degrees Celsius below the tenth percentile minimum ambient temperature in the geographical area and seasonal timeframe in which the B20 is to be used, when tested in accordance with ASTM D 6371.
- (d) **BLENDING.** Blending of diesel fuel and virgin vegetable oil to produce B20 shall be accomplished by one of the methods below.
 - (1) Mechanical mixing or agitation in a tank;
- (2) In-line blending, prior to loading the product into transport equipment, i.e., tank wagon, tank truck, or tractor trailer; or
- (3) Blending via truck manifold which allows blending of the B20 components as they are offloaded if compartmentalized trucks are used.

The resultant product must meet all contract requirements of the desired fuel. Splash blending of B20 is not permitted in receipt tank.

(DESC 52.246-9FEL)

C. ALL OTHER TERMS AND CONDITIONS REMAIN UNCHANGED.